

# Continuum Field Model of Street Canyon: Theoretical Description

## Part 1

Maciej M. Duras  $\star$

Institute of Physics, Cracow University of Technology, ulica Podchorążych 1, PL-30-084  
Cracow, Poland

$\star$  Email: mduras @ riad.usk.pk.edu.pl

*Engng. Trans.* **48**, 415-432 (2000).

### Abstract

A general proecological urban road traffic control idea for the street canyon is proposed with emphasis placed on development of advanced continuum field gasdynamical (hydrodynamical) control model of the street canyon. The continuum field model of optimal control of street canyon is studied. The mathematical physics' approach (Eulerian approach) to vehicular movement, to pollutants' emission, and to pollutants' dynamics is used. The rigorous mathematical model is presented, using gasdynamical (hydrodynamical) theory for both air constituents and vehicles, including many types of vehicles and many types of pollutant (exhaust gases) emitted from vehicles. The six optimal control problems are formulated.

## 1 Description of the model.

In the present article we develop a continuum field model of the street canyon. In the next article we will deal with numerical examples [1]. The vehicular flow in the canyon is multilane bidirectional one-level rectilinear, and it is considered with two coordinated signalized junctions [2, 3, 4]. The vehicles belong to different vehicular classes: passenger cars, and trucks. Emissions from the vehicles are based on technical measurements and many types of pollutants are considered (carbon monoxide CO, hydrocarbons HC, nitrogen oxides NO<sub>x</sub>). The vehicular dynamics is based on a hydrodynamical approach [5]. The governing equations are the continuity equation for the number of vehicles, and Greenshields' equilibrium speed-density u-k model [6].

The model of dynamics of pollutants is also hydrodynamical. The model consists of a set of mutually interconnected nonlinear, three-dimensional, time-dependent, partial differential equations with nonzero right-hand sides (sources), and of boundary and of initial problem. The pollutants, oxygen, and the remaining gaseous constituents of air, are treated as mixture of noninteracting, Newtonian, viscous fluid (perfect or ideal gases). The complete model incorporates as variables the following fields: density of the mixture, mass concentrations of constituents of the mixture, velocity of mixture, temperature of mixture, pressure of mixture, intrinsic (internal) energy of mixture, densities of vehicles, and velocities of vehicles. The

model is based on the assumption of local laws of balance (conservation) of: mass of the mixture, masses of its constituents, momentum and energy of the mixture, the numbers of the vehicles, as well as of the state equations (Clapeyron's law and Greenshields' model). The equations of dynamics are solved by the finite difference scheme.

The six separate monocriterial optimization problems are formulated by defining the functionals of total travel time, of global emissions of pollutants, and of global concentrations of pollutants, both in the studied street canyon and in its two nearest neighbour substitute canyons. The vector of control is a five-tuple composed of two cycle times, two green times, and one offset time between the traffic lights. The optimal control problem consists of minimization of the six functionals over the admissible control domain.

## 2 Assumptions.

The **geometrical assumptions** of the model are as follows:

**G1.** The street canyon is represented by a cuboid:

$$\Omega = [0, a] \times [0, b] \times [0, c], \quad (2.1)$$

with the boundary  $\partial\Omega$  composed of six walls:

$$\partial\Omega = \bigcup_{J=I}^{VI} \partial\Omega_J. \quad (2.2)$$

The structure of the canyon is simplified by the assumption that the walls of the buildings and the road surface are rectangles. If we put the origin of the Cartesian coordinate system  $(x, y, z)$  in cuboid's corner, then we have two canyon walls  $\Omega_{IV}, \Omega_V$ , at  $y = 0, y = b$ , and road's surface  $\Omega_{VI}$ , at  $z = 0$ . The remaining three non-solid open surfaces of air  $\Omega_I, \Omega_{II}, \Omega_{III}$ , have the coordinates  $x = 0, x = a, z = c$ , respectively. We assume that always:

$$(x, y, z) \in \Omega, \quad (2.3)$$

and

$$\begin{aligned} \partial\Omega_I &= \{(x, y, z) \in \Omega : x = 0\}, \\ \partial\Omega_{II} &= \{(x, y, z) \in \Omega : x = a\}, \\ \partial\Omega_{III} &= \{(x, y, z) \in \Omega : z = c\}, \\ \partial\Omega_{IV} &= \{(x, y, z) \in \Omega : y = 0\}, \\ \partial\Omega_V &= \{(x, y, z) \in \Omega : y = b\}, \\ \partial\Omega_{VI} &= \{(x, y, z) \in \Omega : z = 0\}. \end{aligned} \quad (2.4)$$

**G2.** There are neither holes in the walls nor vegetation alongside the road. The remaining three surfaces of the cuboid also do not have holes since they simulate non-solid open rectangles of air.

**G3.** The road sections which constitute the bottom of the street canyon are rectilinear.

**G4.** At each end of the street canyon there are entrance and exit junctions ( $M = 2$ ) with traffic signals (their coordinates are  $x = 0, x = a$ ).

**G5.** The vehicles of  $VT$  distinguishable emission types are material points. The vehicles are treated as hydrodynamical fluid. There are  $n_L = n_1$  left lanes and  $n_2 = n_R$  right ones (the traffic is bidirectional).

The **physical assumptions** of this model are as follows (cf. papers [7] - [50]):

**P1.** The considered mixture of gases consists of  $N = N_E - 1 + N_A$  gases. The first  $N_E - 1 = 3$  gases are the exhaust gases emitted by vehicle engines during combustion ( $\text{CO}, \text{CH}, \text{NO}_x$ , we neglect the presence of  $\text{SO}_2$ ). The remaining  $N_A = 9$  gases are the constituents of air:  $\text{O}_2, \text{N}_2, \text{Ar}, \text{CO}_2, \text{Ne}, \text{He}, \text{Kr}, \text{Xe}, \text{H}_2$  (we neglect the presence of  $\text{H}_2\text{O}, \text{O}_3$ ).

**P2.** The walls of the canyon and the surface of the road are impervious for all gases of the mixture. The remaining three surfaces of the cuboid are pervious for external fluxes of exhaust gases and air constituents.

**P3.** The internal sources of air constituents are not present with the exception of oxygen, *i.e.*,  $N_E$  constituent of the gaseous mixture. There are internal mobile sources of exhaust gases (passenger cars and trucks, with many types of engines: diesel or petrol, and with different ages of engines). During combustion, the engine consumes oxygen, therefore with each internal mobile source of exhaust gases, a negative source of oxygen (sink) is connected.

**P4.** The gaseous mixture is treated as a compressible, Newtonian, and viscous fluid. We assume that also the constituents of the mixture are compressible, Newtonian, and viscous fluids. The constituents do not interact with each other. The  $i$ th constituent possesses individual velocity  $\mathbf{v}_i(x, y, z, t)$ , density  $\rho_i(x, y, z, t)$ , and pressure  $p_i(x, y, z, t)$ , whereas the mixture possesses total velocity  $\mathbf{v}(x, y, z, t)$ , density  $\rho(x, y, z, t)$ , and pressure  $p(x, y, z, t)$ . We assume that

$$\mathbf{v}(x, y, z, t) = \sum_{i=1}^N \frac{\rho_i(x, y, z, t)}{\rho(x, y, z, t)} \cdot \mathbf{v}_i(x, y, z, t), \quad (2.5)$$

$$\rho(x, y, z, t) = \sum_{i=1}^N \rho_i(x, y, z, t), \quad (2.6)$$

$$p(x, y, z, t) = \sum_{i=1}^N p_i(x, y, z, t). \quad (2.7)$$

In order to simplify the set of equations governing the dynamics of mixture, we assume that the total velocity is equal to the velocities of the constituents

$$\mathbf{v}(x, y, z, t) = \mathbf{v}_i(x, y, z, t), i = 1, \dots, N. \quad (2.8)$$

Hence, we can restrict our attention to the equations of balance of total momentum of mixture **E1**, of the total mass of mixture **E2**, of masses of constituents **E3**, and of the energy of mixture **E4**. We assume that the equation of state for mixture **E5** is averaged over the constituents. We also consider equations of balances of the numbers of vehicles **E6**, as well as equations of state for vehicles **E7**.

### 3 Variables.

The following set of descriptive dynamic model variables **A0-A10** together with their boundary **B0-B8** (for  $t \geq 0$ ), and initial conditions **C0-C7** (for  $t = 0$ ), and with the set of equations **E1-E8** that governs their dynamics, is assumed [2]. We always consider

$$(x, y, z, t) \in \Sigma, \Sigma = \Omega \times [0, T_S], \quad (3.1)$$

where  $\Sigma$  is manifold of domains of the fields,  $T_S > 0$  is time of simulation. The border  $\partial\Sigma$  of  $\Sigma$  is composed of six subsets  $\partial\Sigma_J$ :

$$\begin{aligned} \partial\Sigma &= \bigcup_{J=I}^{VI} \partial\Sigma_J, \\ \partial\Sigma_J &= \partial\Omega_J \times [0, T_S], J = I, \dots, VI. \end{aligned} \quad (3.2)$$

- A0.**  $T(x, y, z, t)$ , temperature of the gaseous mixture.
- A1.**  $\mathbf{v}(x, y, z, t)$ , total velocity of the gaseous mixture (compare Eq. (2.5)).
- A2.**  $\rho(x, y, z, t)$ , total density of the gaseous mixture (compare Eq. (2.6)).
- A3.**  $c_i(x, y, z, t)$ , mass concentration of the  $i$ th constituent of gaseous mixture,

$$c_i(x, y, z, t) = \frac{\rho_i(x, y, z, t)}{\rho(x, y, z, t)}, i = 1, \dots, N \quad (3.3)$$

(let us note that due to the condition

$$\sum_{i=1}^N c_i(x, y, z, t) = 1, \quad (3.4)$$

one concentration of the constituent is a dependent variable).

- A4a.**  $p(x, y, z, t)$ , pressure of gaseous mixture (compare Eqs (2.7), (7.16)).

**A4b.**  $p_i(x, y, z, t), i = 1, \dots, N$ , partial pressure of the  $i$ th constituent of gaseous mixture (compare Eqs. (2.7), (7.16), (7.17)).

**A5.**  $k_{l,vt}^s(x, t)$ , density of vehicles of type  $vt$  on the  $l$ th lane measured in  $[\frac{\text{veh}}{\text{m}}]$ , where for  $n_1 = n_L$  lanes  $s = 1$  and  $l$  is the left lane's number,  $l = 1, \dots, n_L$ , whereas for  $n_2 = n_R$  lanes  $s = 2$  and  $l$  is the right lane's number,  $l = 1, \dots, n_R$ ,  $vt$  is the vehicular type number,  $vt = 1, \dots, VT$ .

- A6.**  $\mathbf{w}_{l,vt}^s(x, t)$ , velocity of vehicles of type  $vt$  on the  $l$ th lane.

**A7.**  $e_{l,ct,vt}^s(x, t)$ , emissivity of  $ct$ th constituent of exhaust gases from vehicles of type  $vt$  on  $l$ th lane measured in  $[\frac{\text{kg}}{\text{m}^3 \cdot \text{s}}]$ ,  $ct$  is number of constituent,  $ct = 1, \dots, CT$ .

**A8.**  $\mathbf{u}_m = (g_m, C_m, F)$ , vector of control on the  $m$ th junction,  $m = 1, \dots, M$  ( $M = 2$ ), which contains traffic signals green times  $g_m$ , and cycle times  $C_m$ , and offset time  $F$  between the traffic signals. The vector of control  $\mathbf{u}$  reads:

$$\mathbf{u} = (g_1, C_1, g_2, C_2, F). \quad (3.5)$$

The admissible control domain set  $U^{\text{adm}}$  for this vector in the simulation time period  $T_S$  reads:

$$U^{\text{adm}} = \{(g_1, C_1, g_2, C_2, F) : \quad (3.6)$$

$$g_m \in (g_{m,\min}, g_{m,\max}), C_m \in (C_{m,\min}, C_{m,\max}), F \in (F_{\min}, F_{\max}), m = 1, \dots, M\},$$

whereas  $g_{m,\max} = C_m - g_{m,\text{orth}}$ , where  $g_{m,\text{orth}}$  are green times on orthogonal direction of the junctions (on the canyons orthogonal to the one studied),  $F_{\max} = C_2 - \delta_F$ , where  $\delta_F$  is unit step in direction of  $F$  in parameter space (compare **F0**).

**A9.**  $G_{\text{out}}^m(g_m, C_m, F, t)$ , traffic signal on  $m$ th junction at  $x = x_m$ . For  $x_1 = a$  the traffic signal  $G_{\text{out}}^1$  governs all left lanes (outgoing vehicles) and all right lanes (incoming vehicles), whereas for  $x_2 = 0$  the traffic signal  $G_{\text{out}}^2$  governs all right lanes (outgoing vehicles) and all left lanes (incoming vehicles). For the signals we assume the Boolean output values: GREEN and RED.

**A10.**  $\sigma_{l,vt}^s(x, t)$ , rate of change of linear density of energy connected to heat produced by engines of vehicles of type  $vt$  on  $l$ th lane measured in  $[\frac{\text{J}}{\text{m}\cdot\text{s}}]$ .

## 4 Boundary conditions.

We assume the following boundary conditions [2]:

- B0a-B0c.**  $T|_{\partial\Sigma_K} = T_K|_{\Sigma'_K}$ .
- B0d-B0f.**  $\nabla_{\mathbf{n}} T|_{\partial\Sigma_L} = \vec{0}$ .
- B1a-B1c.**  $\mathbf{v}|_{\partial\Sigma_K} = \mathbf{v}_K|_{\Sigma'_K}$ .
- B1d-B1f.**  $\nabla_{\mathbf{n}} \mathbf{v}|_{\partial\Sigma_L} = \mathbf{0}$ .
- B2a-B2c.**  $\rho|_{\partial\Sigma_K} = \rho_K|_{\Sigma'_K}$ .
- B2d-B2f.**  $\nabla_{\mathbf{n}} \rho|_{\partial\Sigma_L} = \vec{0}$ .
- B3a-B3c.**  $c_i|_{\partial\Sigma_K} = c_{i,K}|_{\Sigma'_K}$ .
- B3d-B3f.**  $\nabla_{\mathbf{n}} c_i|_{\partial\Sigma_L} = \vec{0}$ .
- B4a-B4c.**  $p|_{\partial\Sigma_K} = p_K|_{\Sigma'_K}$ .
- B4d-B4f.**  $\nabla_{\mathbf{n}} p|_{\partial\Sigma_L} = \vec{0}$ .
- B5a-B5d.**  $k_{l,vt}^s(x_m, t) = k_{l,vt,P}^s(t)$ .
- B6a-B6d.**  $\mathbf{w}_{l,vt}^s(x_m, t) = \mathbf{w}_{l,vt,P}^s(t)$ .
- B7a-B7d.**  $e_{l,ct,vt}^s(x_m, t) = e_{l,ct,vt,P}^s(t)$ .
- B8a-B8d.**  $\sigma_{l,vt}^s(x_m, t) = \sigma_{l,vt,P}^s(t)$ .

We define additional sets:

$$\Sigma'_I = \{(y, z, t) : (x, y, z, t) \in \Sigma\} = \Sigma'_{\text{II}}, \quad (4.1)$$

$$\Sigma'_{\text{III}} = \{(x, y, t) : (x, y, z, t) \in \Sigma\},$$

and we assume that  $K = \text{I, II, III}$ ,  $L = \text{IV, V, VI}$ . The gradient operator  $\nabla_{\mathbf{n}}$  works in direction of unit normal outward vector  $\mathbf{n}$  to border  $\partial\Sigma_L$ .  $\nabla_{\mathbf{n}} \mathbf{v}$  is gradient of vector (so it is a tensor of

rank 2),  $\mathbf{O}$  is a zero tensor.  $P = \text{in, out}$ , is the input and output index, and we have the following combinations of triads of indices:  $(s, P, m) = (1, \text{in}, 2), (2, \text{in}, 1), (1, \text{out}, 1), (2, \text{out}, 2)$ , respectively for **B5-B8**. Conditions **B1d-B1f** result from viscosity of the gaseous mixture since the velocity of viscous fluid on immobile and impervious surface is zero. Similarly, conditions **B0d-B0f**, **B2d-B2f**, **B3d-B3f**, **B4d-B4f** result from the fact that the walls and the surface of the road are impervious solid bodies. According to [5], we assume the boundary conditions **B5a-B5d** in the form:

**B5aS-B5dS.**

$$k_{l,vt,P}^s(t) = k_{l,vt,\text{arrival}}^s, \text{ if } G_{\text{out}}^m(C_m, g_m, F, t) = \text{GREEN}, \text{ and } \text{QUEUE}(x_m) = \text{FALSE},$$

$$k_{l,vt,P}^s(t) = k_{l,vt,\text{sat}}^s, \text{ if } G_{\text{out}}^m(C_m, g_m, F, t) = \text{GREEN}, \text{ and } \text{QUEUE}(x_m) = \text{TRUE},$$

$$k_{l,vt,P}^s(t) = k_{l,vt,\text{jam}}^s, \text{ if } G_{\text{out}}^m(C_m, g_m, F, t) = \text{RED},$$

where  $\text{QUEUE}(x_m) = \text{TRUE/FALSE}$  means that there exist/does not exist a queue at  $x = x_m$ , and  $k_{l,vt,\text{arrival}}^s$ ,  $k_{l,vt,\text{sat}}^s$ , and  $k_{l,vt,\text{jam}}^s$ , are arrival, saturation, and jam vehicular densities, respectively (compare Tables 3, and 8 of [1]).

The existence of the queues at the entrances to the canyon (at  $x_2 = 0$  for the left lanes, and at  $x_1 = a$  for the right lanes) is determined by the values of the vehicular densities changing in the following way:

**B5aSS-B5dSS.**

$$k_{l,vt}^s(\xi_s, t) = k_{l,vt,Q}^s, \text{ for } t \in A_Q^s, \quad (4.2)$$

$$A_{\text{GREEN}}^s = [0, T_S] \cap \bigcup_{n=-\infty}^{+\infty} [t_s + nC_1, t_s + nC_1 + g_1), \quad (4.3)$$

$$A_{\text{RED}}^s = [0, T_S] - A_{\text{GREEN}}^s, Q = \text{GREEN, RED}, \quad (4.4)$$

$$\xi_1 = -\delta_x, \xi_2 = a + \delta_x, t_1 = 0, t_2 = F, \quad (4.5)$$

where  $k_{l,vt,\text{GREEN}}^s, k_{l,vt,\text{RED}}^s$ , are green and red vehicular densities, respectively [1], and  $\delta_x$  is the unit step in x-direction in the domain space  $\Sigma$ .

Remark: The functions:  $T_J, \mathbf{v}_J, \rho_J, c_{i,J}, p_J, k_{l,vt,P}^s, \mathbf{w}_{l,vt,P}^s, e_{l,ct,vt,P}^s, \sigma_{l,vt,P}^s$ , are given and they fulfill the natural constraints:

$$\sum_{i=1}^N c_{i,J}(x, y, z, t) = 1. \quad (4.6)$$

## 5 Initial conditions.

The initial conditions are as follows [2]:

**C0.**  $T|_{\Sigma_0} = T_0|_{\Omega}.$

**C1.**  $\mathbf{v}|_{\Sigma_0} = \mathbf{v}_0|_{\Omega}.$

**C2.**  $\rho|_{\Sigma_0} = \rho_0|_{\Omega}.$

**C3.**  $c_i|_{\Sigma_0} = c_{i,0}|_{\Omega}.$

**C4.**  $p|_{\Sigma_0} = p_0|_{\Omega}.$

**C5a-C5b.**  $k_{l,vt}^s(x, 0) = k_{l,vt,0}^s(x).$

**C6a-C6b.**  $\mathbf{w}_{l,vt}^s(x, 0) = \mathbf{w}_{l,vt,0}^s(x)$ .

**C7a-C7b.**  $e_{l,ct,vt}^s(x, 0) = e_{l,ct,vt,0}^s(x)$ .

**C8a-C8b.**  $\sigma_{l,vt}^s(x, 0) = \sigma_{l,vt,0}^s(x)$ .

Remark: The functions:  $T_0, \mathbf{v}_0, \rho_0, c_{i,0}, p_0, k_{l,vt,0}^s, \mathbf{w}_{l,vt,0}^s, e_{l,ct,vt,0}^s, \sigma_{l,vt,0}^s$ , are given and they fulfill the natural constraint:

$$\sum_{i=1}^N c_{i,0}(x, y, z, t) = 1. \quad (5.1)$$

## 6 Sources.

In order to represent the emission process, we assume the following internal sources [2]:

**D0.**  $\sigma(x, y, z, t)$ , the rate of change of the volume density of internal sources of energy connected with the production of heat by vehicular engines, measured in  $[\frac{\text{J}}{\text{m}^3 \cdot \text{s}}]$ . We assume that the sources of energy are situated in  $n_s$  left and right lanes at  $y = y_l^s$ , at the level of the road  $z = 0$ :

$$\sigma(x, y, z, t) = \frac{1}{b \cdot c} \cdot \sum_{s=1}^2 \sum_{l=1}^{n_s} \sum_{vt=1}^{VT} \sigma_{l,vt}^s(x, t) \chi_{D_l^s}(x, y, z), \quad (6.1)$$

where

$$D_l^s = \{(x, y, 0) : (x, y, 0) \in \Omega, y = y_l^s\}, \quad (6.2)$$

are the vehicular lanes, and

$$\chi_D(x, y, z) = \begin{cases} 1 & \text{for } (x, y, z) \in D \\ 0 & \text{for } (x, y, z) \notin D \end{cases}, \quad (6.3)$$

is the characteristic function of set  $D$ .

**D1.**  $S(x, y, z, t)$ , the rate of change of the volume density of internal sources of gaseous mixture consisting of exhaust gases and oxygen, measured in  $[\frac{\text{kg}}{\text{m}^3 \cdot \text{s}}]$ .

**D2.**  $S_{ct}^E(x, y, z, t)$ , the rate of change of the volume density of internal sources (the emission rate) of the  $ct$ th constituent of exhaust gases emitted by all vehicles in the canyon, measured in  $[\frac{\text{kg}}{\text{m}^3 \cdot \text{s}}]$ . We assume that the sources of exhaust gases are situated in  $n_s$  left and right lanes  $y = y_l^s$ , at the level of the road  $z = 0$ :

$$S_{ct}^E(x, y, z, t) = \frac{1}{b \cdot c} \cdot \sum_{s=1}^2 \sum_{l=1}^{n_s} \sum_{vt=1}^{VT} e_{l,ct,vt}^s(x, t) \chi_{D_l^s}(x, y, z). \quad (6.4)$$

$S_{NE}^E(x, y, z, t)$ , the volume density of negative internal sources (the emission rate) of oxygen absorbed by all vehicles in the canyon, measured in  $[\frac{\text{kg}}{\text{m}^3 \cdot \text{s}}]$ . We assume that

$$S_{NE}^E(x, y, z, t) = \text{ONOX} \cdot S_{NE-1}^E(x, y, z, t),$$

where  $\text{ONOX} = -0.5308$ . The following relation holds:

$$S(x, y, z, t) = \sum_{ne=1}^{N_E} S_{ne}^E(x, y, z, t). \quad (6.5)$$

## 7 Equations of dynamics.

Under the above model specifications, the complete set of equations of dynamics of the model is formulated as follows (we follow the general idea presented in [7, 8]):

**E1. Balance of momentum of mixture - Navier Stokes equation.**

$$\rho\left(\frac{\partial \mathbf{v}}{\partial t} + (\mathbf{v} \circ \nabla)\mathbf{v}\right) + S\mathbf{v} = -\nabla p + \eta\Delta\mathbf{v} + \left(\xi + \frac{\eta}{3}\right)\nabla(\operatorname{div}\mathbf{v}) + \mathbf{F}, \quad (7.1)$$

where  $\eta$  is the first viscosity coefficient ( $\eta = 18.1 \cdot 10^{-6} [\frac{\text{kg}}{\text{m}\cdot\text{s}}]$  for air at temperature  $T = 293.16$  [K]),  $\xi$  is the second viscosity coefficient ( $\xi = 15.6 \cdot 10^{-6} [\frac{\text{kg}}{\text{m}\cdot\text{s}}]$  for air at temperature  $T = 293.16$  [K], compare [51]),  $\mathbf{F} = \rho\mathbf{g}$  is the gravitational body force density,  $\mathbf{g}$  is the gravitational acceleration of Earth ( $\mathbf{g} = (0, 0, -9.81) [\frac{\text{m}}{\text{s}^2}]$ ),  $\nabla\mathbf{v}$  is gradient of the vector (so it is a tensor of rank 2). We assume that the gaseous mixture is a compressible and viscous fluid.

**E2. Balance of mass of mixture - Equation of continuity.**

$$\frac{\partial \rho}{\partial t} + \operatorname{div}(\rho\mathbf{v}) = S. \quad (7.2)$$

We have assumed the source **D1**.

**E3. Balances of masses of constituents of mixture - Diffusion equations.**

**E3a.**

$$\begin{aligned} \rho\left(\frac{\partial c_i}{\partial t} + \mathbf{v} \circ \nabla c_i\right) &= S_i^E - c_i S + \\ &+ \sum_{m=1}^{N-1} \{(D_{im} - D_{iN}) \cdot \operatorname{div}[\rho \nabla(c_m + \frac{k_{T,m}}{T} \nabla T)]\}, i = 1, \dots, N_E. \end{aligned} \quad (7.3)$$

**E3b.**

$$\begin{aligned} \rho\left(\frac{\partial c_i}{\partial t} + \mathbf{v} \circ \nabla c_i\right) &= -c_i S + \\ &+ \sum_{m=1}^{N-1} \{(D_{im} - D_{iN}) \cdot \operatorname{div}[\rho \nabla(c_m + \frac{k_{T,m}}{T} \nabla T)]\}, i = (N_E + 1), \dots, N, \end{aligned} \quad (7.4)$$

where  $D_{im} = D_{mi}$  is the mutual diffusivity coefficient from the  $i$ -th constituent to  $m$ -th one, and  $D_{ii}$  is the autodiffusivity coefficient of the  $i$ -th constituent, and  $k_{T,m}$  is the thermodiffusion ratio of the  $m$ -th constituent. The diffusivity coefficients and thermodiffusion ratios are constant and known (compare [52]). In **E3a** we have assumed the sources **D1-D2**. In **E3b** only the source **D1** is taken into account. Since the mixture is in motion, we cannot neglect the convection term:  $\mathbf{v} \circ \nabla c_i$ . We assume that the barodiffusion and gravitodiffusion coefficients are equal to zero.

**E4. Balance of energy of mixture.**

$$\rho\left(\frac{\partial \epsilon}{\partial t} + \mathbf{v} \circ \nabla \epsilon\right) = -\left(-\frac{1}{2}\mathbf{v}^2 + \epsilon\right)S + \mathbf{T} : \nabla \mathbf{v} + \operatorname{div}(-\mathbf{q}) + \sigma, \quad (7.5)$$



where  $\epsilon$  is the mass density of intrinsic (internal) energy of the air mixture,  $\mathbf{T}$  is the stress tensor, symbol  $:$  denotes the contraction operation,  $\mathbf{q}$  is the vector of flux of heat. We assume that [2]:

$$\epsilon = \sum_{i=1}^N \epsilon_i, \quad (7.6)$$

$$\begin{aligned} \epsilon_i &= \frac{1}{m_i} \left\{ c_i k_B T \exp\left(-\frac{m_i |\mathbf{g}| z}{k_B T}\right) \cdot \left[ \left(-\frac{z}{c}\right) \cdot \left(1 - \exp\left(-\frac{m_i |\mathbf{g}| c}{k_B T}\right)\right) - \exp\left(-\frac{m_i |\mathbf{g}| c}{k_B T}\right) \right] \right\} + \\ &+ \tilde{\mu}_i c_i, \\ \tilde{\mu}_i &= \frac{\mu_i}{m_i}, \end{aligned} \quad (7.7)$$

$$\mu_i = k_B T \cdot \left\{ \ln[(c_i p)(k_B T)^{-\frac{c_{p,i}}{k_B}} \left(\frac{m_{\text{air}}}{m_i}\right) \left(\frac{2\pi h^2}{m_i}\right)^{\frac{3}{2}}] \right\} + m_i |\mathbf{g}| z, \quad (7.8)$$

$$\begin{aligned} T_{mk} &= -p \delta_{mk} + \\ &+ \eta \cdot \left[ \left( \frac{\partial v_m}{\partial x_k} + \frac{\partial v_k}{\partial x_m} - \frac{2}{3} \delta_{mk} \text{div}(\mathbf{v}) \right) \frac{\partial v_k}{\partial x_m} \right] + \xi \cdot [(\delta_{mk} \text{div}(\mathbf{v}))^2], \quad m, k = 1, \dots, 3, \end{aligned} \quad (7.9)$$

$$\mathbf{T} : \nabla \mathbf{v} = \sum_{m=1}^3 \sum_{k=1}^3 T_{mk} \frac{\partial v_m}{\partial x_k}, \quad (7.10)$$

$$\mathbf{q} = \sum_{i=1}^N \left\{ \left[ \left( \frac{\beta_i T}{\alpha_{ii}} + \tilde{\mu}_i \right) \mathbf{j}_i \right] + [(-\kappa) \nabla T] \right\}, \quad (7.11)$$

$$\mathbf{j}_i = -\rho D_{ii} \left( c_i + \frac{k_{T,i}}{T} \nabla T \right), \quad (7.12)$$

$$\alpha_{ii} = \frac{[\rho D_{ii}]}{\left[ \left( \frac{\partial \tilde{\mu}_i}{\partial c_i} \right)_{(c_n)_{n=1, \dots, N, i \neq n}, T, p} \right]}, \quad (7.13)$$

$$\beta_i = [\rho D_{ii}] \cdot \left\{ \frac{k_{T,i}}{T} - \frac{\left[ \left( \frac{\partial \tilde{\mu}_i}{\partial T} \right)_{(c_n)_{n=1, \dots, N, p}} \right]}{\left[ \left( \frac{\partial \tilde{\mu}_i}{\partial c_i} \right)_{(c_n)_{n=1, \dots, N, i \neq n}, T, p} \right]} \right\}, \quad (7.14)$$

where  $\epsilon_i$  is the mass density of intrinsic (internal) energy of the  $i$ th constituent of the air mixture,  $m_i$  the molecular mass of the  $i$ th constituent,  $k_B = 1.3807 \cdot 10^{-23} [\frac{\text{J}}{\text{kg}}]$  is Boltzmann's constant,  $\mu_i$  is the complete partial chemical potential of the  $i$ th constituent of the air mixture (it is complete since it is composed of chemical potential without external force field and of external potential),  $m_{\text{air}} = 28.966 [\text{u}]$  is the molecular mass of air ( $1[\text{u}] = 1.66054 \cdot 10^{-27} [\text{kg}]$ ),  $\delta_{mk}$  is Kronecker's delta,  $c_{p,i}$  is the specific heat at constant pressure of the  $i$ th constituent of air mixture,  $h = 6.62608 \cdot 10^{-34} [\text{J} \cdot \text{s}]$  is Planck's constant,  $\mathbf{j}_i$  is the vector of flux of mass of the  $i$ th constituent of the air mixture, and  $\kappa$  is the coefficient of thermal conductivity of air. These magnitudes are derived from Grand Canonical ensemble with external gravitational Newtonian field.

**E5. Equation of state of the mixture - Constitutive equation - Clapeyron's equation.**

$$\frac{p}{\rho} = \frac{R}{m_{\text{air}}} \cdot T \quad (7.16)$$

is Clapeyron's equation of state for a gaseous mixture, where  $R = 8.3145 \left[ \frac{\text{J}}{\text{mole} \cdot \text{K}} \right]$  is the gas constant.

$$p_i = c_i \cdot \frac{m_{\text{air}}}{m_i} \cdot p \quad (7.17)$$

are partial pressures of constituents according to Dalton's law.

**E6. Balances of numbers of vehicles - Equations of continuity of vehicles.**

$$\frac{\partial k_{l,vt}^s}{\partial t} + \text{div}(k_{l,vt}^s \mathbf{w}_{l,vt}^s) = 0. \quad (7.18)$$

**E7. Equations of state of vehicles - Greenshields model.**

$$\mathbf{w}_{l,vt}^s(x, t) = (w_{l,vt,f}^s \cdot (1 - \frac{k_{l,vt}^s(x, t)}{k_{l,vt,jam}^s}), 0, 0). \quad (7.19)$$

The Greenshields equilibrium speed-density u-k model is assumed [6]. The values of maximum free flow speed  $w_{l,vt,f}^s$ , and of jam vehicular densities  $k_{l,vt,jam}^s$ , are given in Tables 3 and 8 of [1].

**E8. Technical parameters.**

The dependence of emissivity on the density and velocity of vehicles is assumed in the form [54]:

**E8a.**

$$e_{l,ct,vt}^s(x, t) = k_{l,vt}^s(x, t) \cdot \left[ \left( \frac{|\mathbf{w}_{l,vt}^s(x, t)| - \tilde{w}_{ct,vt,i_l}}{\tilde{w}_{ct,vt,i_l+1} - \tilde{w}_{ct,vt,i_l}} \right) \cdot (\tilde{e}_{ct,vt,i_l+1} - \tilde{e}_{ct,vt,i_l}) + \tilde{e}_{ct,vt,i_l} \right], \quad (7.20)$$

where  $\tilde{w}_{ct,vt,i_l}$  are experimental velocities,  $|\mathbf{w}_{l,vt}^s(x, t)| \in (\tilde{w}_{ct,vt,i_l}, \tilde{w}_{ct,vt,i_l+1})$ ,  $\tilde{e}_{ct,vt,i_l}$ , are experimental emissions of the  $ct$ th exhaust gas from single vehicle of  $vt$ th type at velocities  $\tilde{w}_{ct,vt,i_l}$ , respectively, measured in  $\left[ \frac{\text{kg}}{\text{veh} \cdot \text{s}} \right]$ ,  $i_l = 1, \dots, N_{EM}$ ,  $N_{EM}$  is the number of experimental measurements. Similarly, the dependence of the change of the linear density of energy on the density and velocity of vehicles is taken in the form:

**E8b.**

$$\sigma_{l,vt}^s(x, t) = q_{vt} \cdot k_{l,vt}^s(x, t) \cdot \left[ \left( \frac{|\mathbf{w}_{l,vt}^s(x, t)| - \bar{w}_{vt,i_l}}{\bar{w}_{vt,i_l+1} - \bar{w}_{vt,i_l}} \right) \cdot (\sigma_{vt,i_l+1} - \sigma_{vt,i_l}) + \sigma_{vt,i_l} \right], \quad (7.21)$$

where  $\sigma_{vt,i_l}$ , are experimental values of consumption of gasoline/diesel for a single vehicle of  $vt$ th type at velocities  $\bar{w}_{vt,i_l}$ , respectively, measured in  $\left[ \frac{\text{kg}}{\text{veh} \cdot \text{s}} \right]$ ,  $q_{vt}$  is the emitted combustion energy per unit mass of gasoline/diesel  $\left[ \frac{\text{J}}{\text{kg}} \right]$  (compare [53]).

## 8 Optimization problems.

Our control task is the minimization of the measures of the total travel time (TTT) [5], emissions (E), and concentrations (C) of exhaust gases in the street canyon, therefore the appropriate optimization problems may be formulated as follows [2]:

### F0. Vector of control.

$$\mathbf{u} = (g_1, C_1, g_2, C_2, F) \in U^{\text{adm}}, \quad (8.1)$$

where  $\mathbf{u}$  is vector of boundary control,  $g_m$  are green times,  $C_m$  are cycle times,  $F$  is offset time, and  $U^{\text{adm}}$  is a set of admissible control variables (compare **A8**, **A9**, **B5**, **B5S**, **B5SS**).

We define six functionals **F1-F6** of the total travel time, emissions, and concentrations of pollutants in single canyon, and in canyon with the nearest neighbour substitute canyons, respectively.

### F1. Total travel time for a single canyon.

$$J_{\text{TTT}}(\mathbf{u}) = \sum_{s=1}^2 \sum_{l=1}^{n_s} \sum_{vt=1}^{VT} \int_0^a \int_0^{T_S} k_{l,vt}^s(x, t) dx dt. \quad (8.2)$$

### F2. Global emission for a single canyon.

$$J_{\text{E}}(\mathbf{u}) = \sum_{s=1}^2 \sum_{l=1}^{n_s} \sum_{ct=1}^{CT} \sum_{vt=1}^{VT} \int_0^a \int_0^{T_S} e_{l,ct,vt}^s(x, t) dx dt. \quad (8.3)$$

### F3. Global pollutants concentration for a single canyon.

$$J_{\text{C}}(\mathbf{u}) = \rho_{\text{STP}} \cdot \sum_{i=1}^{N_E-1} \int_0^a \int_0^b \int_0^c \int_0^{T_S} c_i(x, y, z, t) dx dy dz dt. \quad (8.4)$$

### F4. Total travel time for the canyon in street subnetwork.

$$\begin{aligned} J_{\text{TTT,ext}}(\mathbf{u}) &= J_{\text{TTT}}(\mathbf{u}) + \\ &+ a \cdot \sum_{s=1}^2 \alpha_{\text{TTT,ext}}^s \sum_{l=1}^{n_s} \sum_{vt=1}^{VT} k_{l,vt,\text{jam}}^s \cdot (C_s - g_s). \end{aligned} \quad (8.5)$$

### F5. Global emission for the canyon in street subnetwork.

$$\begin{aligned} J_{\text{E,ext}}(\mathbf{u}) &= J_{\text{E}}(\mathbf{u}) + \\ &+ a \cdot \sum_{s=1}^2 \alpha_{\text{E,ext}}^s \sum_{l=1}^{n_s} \sum_{ct=1}^{CT} \sum_{vt=1}^{VT} e_{l,ct,vt,\text{jam}}^s \cdot (C_s - g_s). \end{aligned} \quad (8.6)$$

### F6. Global pollutants concentration for the canyon in street subnetwork.

$$\begin{aligned} J_{\text{C,ext}}(\mathbf{u}) &= J_{\text{C}}(\mathbf{u}) + \\ &+ \rho_{\text{STP}} \cdot a \cdot b \cdot c \cdot \sum_{i=1}^{N_E-1} c_{i,\text{STP}} \cdot \sum_{s=1}^2 \alpha_{\text{C,ext}}^s \cdot (C_s - g_s). \end{aligned} \quad (8.7)$$

The integrands  $k_{l,vt}^s, e_{l,ct,vt}^s, c_i$  in functionals **F1-F6** depend on the control vector **u** **F0** through the boundary conditions **B0-B8**, through the equations of dynamics **E1-E8**, as well as, through the sources **D0-D2**. The value of the vector of control  $u$  directly affects the boundary conditions **B5, B5S, B5SS**, and then the boundary conditions **B6-B8** for vehicular densities, velocities, and emissivities. It also affects the sources **D0-D2**. Next, it propagates to the equations of dynamics **E1-E8** and then it influences the values of functionals **F1-F6**. We only deal with six monocriterial optimization problems **O1-O6**, and not with one multicriterial problem. We put the scaling parameters equal to unity:  $\alpha_{TTT,ext}^s = \alpha_{E,ext}^s = \alpha_{C,ext}^s = 1.0$ , in functionals **F4-F6**.  $\rho_{STP}$  is the density of air at standard temperature and pressure STP,  $c_{i,STP}$  is concentration of the  $i$ th constituent of air at standard temperature and pressure.  $J_{TTT}$  and  $J_{TTT,ext}$  are measured in  $[veh \cdot s]$ ,  $J_E$  and  $J_{E,ext}$  are measured in  $[kg]$ , and  $J_C$  and  $J_{C,ext}$  are measured in  $[kg \cdot s]$ , respectively.

Now we formulate six separate monocriterial optimization problems **O1-O6** that consist in minimization of functionals **F1-F6** with respect to control vector **F0** over admissible domain, while the equations of dynamics **E1-E8** are fulfilled.

**O1. Minimization of total travel time for a single canyon.**

$$J_{TTT}^* = J_{TTT}(\mathbf{u}_{TTT}^*) = \min\{\mathbf{u} \in U^{adm} : J_{TTT}(\mathbf{u})\}; \quad (8.8)$$

**O2. Minimization of global emission for a single canyon.**

$$J_E^* = J_E(\mathbf{u}_E^*) = \min\{\mathbf{u} \in U^{adm} : J_E(\mathbf{u})\}; \quad (8.9)$$

**O3. Minimization of global pollutants concentration for a single canyon.**

$$J_C^* = J_C(\mathbf{u}_C^*) = \min\{\mathbf{u} \in U^{adm} : J_C(\mathbf{u})\}; \quad (8.10)$$

**O4. Minimization of total travel time for a canyon in street subnetwork.**

$$J_{TTT,ext}^* = J_{TTT,ext}(\mathbf{u}_{TTT,ext}^*) = \min\{\mathbf{u} \in U^{adm} : J_{TTT,ext}(\mathbf{u})\}; \quad (8.11)$$

**O5. Minimization of global emission for a canyon in street subnetwork.**

$$J_{E,ext}^* = J_{E,ext}(\mathbf{u}_{E,ext}^*) = \min\{\mathbf{u} \in U^{adm} : J_{E,ext}(\mathbf{u})\}; \quad (8.12)$$

**O6. Minimization of global pollutants concentration for a canyon in street subnetwork.**

$$J_{C,ext}^* = J_{C,ext}(\mathbf{u}_{C,ext}^*) = \min\{\mathbf{u} \in U^{adm} : J_{C,ext}(\mathbf{u})\}, \quad (8.13)$$

where  $J_{TTT}^*, J_E^*, J_C^*, J_{TTT,ext}^*, J_{E,ext}^*, J_{C,ext}^*$ , are the minimal values of the functionals **F1-F6**, and  $\mathbf{u}_{TTT}^*, \mathbf{u}_E^*, \mathbf{u}_C^*, \mathbf{u}_{TTT,ext}^*, \mathbf{u}_{E,ext}^*, \mathbf{u}_{C,ext}^*$ , are control vectors at which the functionals reach the minima, respectively.

## 9 Acknowledgements

It is my pleasure to thank Professor Andrzej Adamski for formulating the problem, Professors Stanisław Białas, Wojciech Mitkowski, and Gwidon Szefer, for many constructive criticisms. I also thank Professor Włodzimierz Wójcik for his giving me the access to his computer facilities.

## References

- [1] M. M. DURAS, Continuum Field Model of Street Canyon: Numerical Examples, Engineering Transactions, 1999, submitted.
- [2] M. M. DURAS, Road Traffic Control in Street Canyons, Ph. D. Thesis, University of Mining and Metallurgy, Cracow, August 1998, pp. 1-363, 1998.
- [3] A. ADAMSKI, and M. M. DURAS, Environmental Traffic Control Issues in Street Canyons, Polish Journal of Environmental Studies, **6**, 1, 13-20, 1997.
- [4] A. ADAMSKI, and M. M. DURAS, Air Pollution Optimal Traffic Control Issues in Integrated Street, Polish Journal of Environmental Studies, **8**, 1, 7-17, 1999.
- [5] P. G. MICHALOPOULOS, D. E. BESKOS, and J.-K. LIN, Analysis of Interrupted Traffic Flow by Finite Difference Methods, Transportation Research-B, **18B**, 4/5, 409-421, 1984.
- [6] B. D. GREENSHIELDS, A study of traffic capacity, Proceedings of Highway Research Board, **14**, pp. 448-477, 1934.
- [7] A. CEMAL ERINGEN, and G. A. MAUGIN, Electrodynamics of Continua, Springer-Verlag, New York, 1990 Vol. I, Chapters 3, 5; Vol. II, Chapters 9, 10.
- [8] L. D. LANDAU, and E. M. LIFSHITZ, Theoretical Physics: Hydrodynamics, Nauka, Moscow, 1986, Chapters 2, 6 [in Russian].
- [9] S. L. SOO, Fluid Dynamics of Multiphase Systems, Series Titles: A Blaisdell Book in the Pure and Applied Sciences, Blaisdell Publishing Company, A Division of Ginn and Company, Waltham: Massachusetts, Massachusetts, Toronto, London, 1967, Chapters 6, 7, 8.
- [10] Continuum Physics, A. Cemal Eringen, Ed., Contributors: A. Cemal Eringen and others, Academic Press, New York, San Francisco, London, 1971-1976, Vol. 1, Mathematics; Vol. 2, Continuum Mechanics of Single-Substance Bodies; Vol. 3, Mixtures and EM Field Theories; Vol. 4, Polar and Non-Local Field Theories; Vol. 1, Part 1; Vol. 3, Part 1; Vol. 4, Part 1.
- [11] A. CEMAL ERINGEN, Nonlinear Theory of Continuous Media, McGraw-Hill Book Company, Inc., New York, San Francisco, Toronto, London, 1962, Chapters 2, 3, 4, 5, 7.
- [12] H. LAMB, Hydrodynamics, Dover Publications, New York, 1945, Chapter 1.
- [13] I. I. OL'KHOVSKIY, Course of Theoretical Mechanics for Physicists, Moscow University Press, Moscow, 1974, Part 2 [in Russian].

- [14] G. A. MAUGIN, Continuum Mechanics of Electromagnetic Solids, North-Holland Series in Applied Mathematics and Mechanics; Vol. 33; North-Holland, Amsterdam, New York, Oxford, Tokyo, 1988, Chapter 2.
- [15] L. G. LOYTZYANSKIY, Mechanics of Liquids and Gases, State Editorial of Technical-Theoretical Literature, Moscow, 1958, Chapters 1, 2, 3, 4, 8, 10 [in Russian].
- [16] Computational Mechanics '88: Theory and Applications: Proceedings of the International Conference on Computational Engineering Science, April 10-14, 1988, Atlanta, Georgia, USA, S. N. Atluri, and G. Yagawa, Eds., Springer-Verlag, Berlin, Heidelberg, New York, London, Paris, Tokyo, Volumes 1, 2, 1988, Vol. 1, Sessions 1, 7; Vol. 2, Sessions 33, 36, 38, 52, 53, 54, 55, 56, 58, 59.
- [17] E. BECKER, Gas Dynamics, B. G. Teubner, Stuttgart, 1969, Chapters 1, 2 [in German].
- [18] L. I. SYEDOV, Mechanics of Continuum Medium, Nauka, Moscow, Volumes 1, 2, 1970-1972, Vol. 1, Chapters 3, 4, 5, 7; Vol. 2, Chapter 8 [in Russian].
- [19] SHIH-I PAI, Viscous Flow Theory, D. Van Nostrand Company, Inc., Toronto, Princeton, New Jersey, New York, London, Volumes 1, 2, 1956-1957, Vol. 1, Laminar Flow; Vol. 2, Turbulent Flow, Vol. 1, Chapters 1, 2, 3, 6.
- [20] T. OROVEANU, Mechanics of Viscous Fluids, Editorial of Academy of Popular Republic of Romania, Bucureşti, 1967, Chapters 1, 2, 3, 4 [in Romanian].
- [21] L. M. MILNE-THOMSON, Theoretical Hydrodynamics, The Macmillan Company, New York, 1950, Chapter 3.
- [22] Transport with Chemical Reactions, P. Stroeve, and W. J. Ward, Eds, AIChE Symposium Series, Vol. 77, Number 202, American Institute of Chemical Engineers, New York, 1981.
- [23] M. BARRÈRE, and R. PRUD'HOMME, Fundamental Equations of the Aerothermochemistry, Masson et Compagnie, Éditeurs, Paris, 1973, Chapters 2, 3, 4 [in French].
- [24] R. L. LIBOFF, Introduction to the Theory of Kinetic Equations, John Wiley and Sons, Inc., New York, London, Sydney, Toronto, 1969, Chapter 3.
- [25] G. A. BIRD, Molecular Gas Dynamics, Clarendon Press, Oxford University Press, Oxford Engineering Science Series, Oxford, 1976, Chapters 9, 11, 12.
- [26] Z. G. SZABO, Advances in the Kinetics of Homogeneous Gas Reactions, Methuen and Company Ltd, London, 1964, Chapters 2, 3, 4, 7, 8 [in German].
- [27] Kinetic Processes in Gases and Plasmas, A. R. Hochstim, Ed., Academic Press, New York, London, 1969, A Volume in the Reentry Physics Series, Chapters 2, 3, 7.

- [28] J. F. CLARKE, and M. McCHESNEY, Dynamics of Relaxing Gases, Butterworths and Company Publishers, London, Boston, 1975, Chapter 2.
- [29] G. N. ABRAMOVICH, Applied Gas Dynamics, Nauka, Moscow, 1969, Chapter 2 [in Russian].
- [30] H. ROUSE, Elementary Mechanics of Fluids, John Wiley and Sons, New York; Chapman and Hall Limited, Inc., 1946, Chapter 4.
- [31] Lecture Notes in Physics, Vol. 31, Transport Phenomena, J. Ehlers, K. Hepp, H. A. Weidenmüller, Eds; Sitges International School of Statistical Mechanics, 1974. Transport phenomena: Sitges International School of Statistical Mechanics, June 1974, Sitges, Barcelona/Spain, G. Kirczenow, and J. Marro, Eds, Springer-Verlag, Berlin, Heidelberg, New York, 1974.
- [32] Lecture Notes in Engineering, Vol. 18, C. A. Brebbia, and S. A. Orszag, Eds; Numerical Simulation of Fluid Flow and Heat/Mass Transfer Processes; International PHOENICS Users Conference [1st: 1985: Dartford Campus of Thames Polytechnic], N. C. Markatos, D. G. Tatchell, M. Gross, and N. Rhodes, Eds, Springer-Verlag, Berlin, Heidelberg, New York, Tokyo, 1986, Session 9.
- [33] W. M. ZAJĄCZKOWSKI, On Nonstationary Motion of a Compressible Barotropic Viscous Fluid Bounded by a Free Surface, Dissertationes Mathematicae, Vol. CCCXXIV, Institute of Mathematics, Polish Academy of Sciences, Warsaw, 1993.
- [34] S. PANCHEV, Random Functions and Turbulence, Hydrometeorological Editorial, Sankt Petersburg, 1967, Parts 2, 3 [in Russian].
- [35] C. JACOB, Mathematical Introduction to Fluid Mechanics, Gauthier-Villars Editeur-Imprimeur-Libraire, Paris, Parts 2, 3, 4 [in French].
- [36] T. N. ABRAMYENKO, Thermal Diffusion in Gases, Science and Technics, Minsk, 1982, Chapters 1, 2, 3, 4 [in Russian].
- [37] Combustion Chemistry, W. C. Gardiner, Jr., Ed., Springer-Verlag, New York, Berlin, Heidelberg, Tokyo, 1984, Chapters 1, 2, 3, 5, 7, 8.
- [38] S. POSTRZEDNIK, Thermodynamics of Flows, Selected Irreversible Flows and Molecular Flows, Silesian Technical University, University Lectures No. 1784, Gliwice, 1993, Chapter 2 [in Polish].
- [39] CHIA-SHUN YIH, Dynamics of Nonhomogeneous Fluids; Macmillan Series in Advanced Mathematics and Theoretical Physics, M. Kac, M. Hall, Jr., C. C. Lin, I. Stakgold, G. E. Uhlenbeck, Editorial Board, The Macmillan Company, New York; Collier-Macmillan Limited, London, 1965, Chapter 1.

- [40] S. CHAPMAN, and T. G. COWLING, The Mathematical Theory of Non-Uniform Gases, Cambridge University Press, Cambridge, 1970, Chapters 2, 6, 9, 10, 12, 13, 14, 18.
- [41] H. ERBRINK, Turbulent Diffusion from Tall Stacks; The Use of Advanced Boundary-Layer Meteorological Parameters in the Gaussian Dispersion Model “STACKS”, Free University of Amsterdam Press, Ph. D. Thesis, Amsterdam, 1995.
- [42] E. SZÜCS, Engineering Models, Müszaki Könyvkiadó, Budapest, 1972, Chapters 3, 10, 11 [in Hungarian].
- [43] D. TELIONIS, Unsteady Viscous Flows; Springer Series in Computational Physics, Springer-Verlag, New York, 1981, Chapter 2.
- [44] Lecture Notes in Physics, Vol. 271; Nonlinear Hydrodynamic Modeling: a Mathematical Introduction, H. N. Shিরer, Ed., Springer-Verlag, Berlin, New York, 1987.
- [45] J. A. DUTTON, and R. WELLS, in: Lecture Notes in Physics, Vol. 271; Nonlinear Hydrodynamic Modeling: a Mathematical Introduction, H. N. Shিরer, Ed., Springer-Verlag, Berlin, New York, 1987, p. 444.
- [46] V. V. KAFAROV, Fundamentals of Mass Transfer, Mir, Moscow, 1975, Chapter 12.
- [47] Recent Developments in Theoretical and Experimental Fluid Mechanics: Compressible and Incompressible Flows, U. Müller, K. G. Roesner, B. Schmidt, and J. Zierep, Eds, Springer-Verlag, Berlin, New York, 1979.
- [48] W. SCHÖNHAEUER, H.-G. DÄUBLER, and G. GLOTZ, in: Recent Developments in Theoretical and Experimental Fluid Mechanics: Compressible and Incompressible Flows, U. Müller, K. G. Roesner, B. Schmidt, and J. Zierep, Eds, Springer-Verlag, Berlin, New York, 1979, p. 257.
- [49] A. D. KOVALYENKO, Principles of Thermoelasticity, Naukova Dumka, Kiev, 1970, Chapters 1, 2, 3 [in Russian].
- [50] N. V. SALTANOV, Analytical Hydromechanics, Naukova Dumka, Kiev, 1984, Chapters 1, 2, 4 [in Russian].
- [51] G. J. PRANGSMA, A. H. ALBERGA, and J. J. M. BEENAKKER, Ultrasonic determination of the volume viscosity of N<sub>2</sub>, CO, CH<sub>4</sub>, and CD<sub>4</sub> between 77 and 300K, Physica, **64**, 2, 278-288, 1973.
- [52] S. CHAPMAN, and T. G. COWLING, The Mathematical Theory of Non-Uniform Gases, Cambridge University Press, Cambridge, 1970, Table No. 22, p. 263; Table No. 24, p. 266; Table No. 25, p. 267.



- [53] H. S. EGGLESTON, D. GAUDIOSO, N. GORISSEN, R. JOUMARD, R. C. RIJKE-BOER, Z. SAMARAS, and K.-H. ZIEROCK, CORINAIR Working Group on Emission Factors for Calculating 1990 Emissions from Road Traffic Office for Official Publications of the European Communities, ECSC-EEC-EAEC, Brussels-Luxembourg, Brussels-Luxembourg, 1993, Vol. 1.
- [54] A. STURM, University of Graz Report, 1996 [private communication].
- [55] M. BRZEŹAŃSKI, Evaluation of Transport Emission of the Amount on a Chosen Section of the Road Network in Cracow, KONMOT'98, Table 2, 1998 [in Polish].